

Polymaster UK Ltd
Unit 19, Upper mills
Slaithwaite
Huddersfield
HD7 5HA
UK

T: +44 (0) 1484 847464
F: +44 (0) 1484 847750
E: enquiry@polymaster.co.uk
W: www.polymaster.co.uk

Polymaster PM-IV

with automatic edge guidance



PM-IV with additional cutter, inclined top and MM-II counter

Technical Data

- Cradle	6 rollers
- Max roll width	180 cm (71")
- Inspection surface	600 mm (24")
- ON / OFF switch	foot operated
- Max re-roll diameter	400 mm (15")
- Operating speed	0-45 m/min
- Motor	1x230 V/50 Hz 1x120 V/60 Hz
- Dimensions	width 245 cm (97") depth 150 cm (59") height 111 cm (44")
- Weight	302 kg / 665 lbs

Subject to design changes

- State of the art rolling machine
- Automatic edge guidance for high quality roll presentation
- Measuring
- Large inspection area
- Cut length
- Foot operated on/off switch
- Speed control
- Reverse capability
- Emergency stop
- Locking wheels allow easy movement
- Heavy duty option for roll diameter up to 50cm
- Available with optional cutters, counters, light box, power rear cradle, inclined top, lazy-loop system with clutch, and storage shelves

POLYmaster

